

4				
ITEM NO.	PART NO.	MODEL	DESCRIPTION	QTY.
1	1263852	NUS-0010	NUT,HEX,1/4-28,SS	1
2	1074233	424-JE	DISC, 424, EP	1
3	1073948	200-GG	GASKET,COPPER,1/200X1/4ID	1
4	1262436	-	LOCTITE 565 POLYTUBE	1
5	15243	ORE-028	O-RING,-028,EP	1
6	1071726	ORE-110TC	O-RING, -110, EPDM, TEFLON COATED	1
7	1071734	ORE-132	O-RING, EPDM -132	1
8	42561	-	LUBRICANT,SILICONE,PACKET	1
9	1263853	RMET	HEX NUT 5/16" - 24	1
10	1074252	424-R	COPPER GASKET	1
11	1074224	424-FV	DIAPHRAGM,424,FKM	1

1074253 SEAL AND DIAPHRAGM KIT
ASSEMBLY INSTRUCTION
MODEL NO. 424-RAEFV






REVISIONS				
ECN	REV	DESCRIPTION	DATE	APPROVED
2436	A	INITIAL RELEASE	9/4/2024	PMJ

STEP 1
(WITH ONE PIECE SHAFT)

STEP 2

STEP 3
(NOT NEEDED FOR MOST REPAIRS)




LEGACY TWO PIECE SHAFT



STEP 4

STEP 5

STEP 6



- NOTES:
- ALL O-RINGS MUST BE INSTALLED WITH 42561 SILICONE LUBRICANT.
 - ACTUAL TORQUE MAY BE WITHIN 10% OF NOMINAL VALUE IN TABLE.
 - LEGACY TWO PIECE SHAFT USES A COPPER GASKET BETWEEN SHAFT AND DISC HOLDER.

TORQUE TABLE	
PART	TORQUE
SEAT	120 IN.LBS.
UPPER SHAFT NUT	90 IN.LBS.
LOWER SHAFT NUT	90 IN.LBS.
SHAFT GUIDE	120 IN.LBS.
CAP SCREWS & NUTS	140 IN.LBS.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M -2018.

PRIMARY UNITS SHOWN IN INCHES.
SECONDARY UNITS SHOWN IN MILLIMETERS.

DEFAULT TOLERANCES:
ANGLES : ± 1°
1 PLACE .X: ± .100 [2.54]
2 PLACE .XX: ± .010 [0.3]
3 PLACE .XXX: ± .005 [0.13]

THIS DOCUMENT IS SOLELY THE PROPERTY OF AQ-MATIC.
REPRODUCTION, USE DISCLOSURE, OR TRANSMISSION OF THIS
DOCUMENT OR DETAILS CONTAINED HEREIN, IN PART OR IN WHOLE,
IS PROHIBITED WITHOUT THE WRITTEN CONSENT OF AQ-MATIC
ENGINEERING. THIS DOCUMENT AND ANY COPIES SHALL BE
RETURNED TO AQ-MATIC UPON WRITTEN REQUEST.

DESCRIPTION			
KIT,424,D&S,-EP/-FV			
DWG NO.	1074253	REV.	A
SIZE	C	SCALE	1:2
SHEET 1 OF 1			