



V46 SERIES DIAPHRAGM VALVE MASTER CHART

* FILL IN PROPER DESIGNATIONS TO DETERMINE PRODUCT NUMBER: V 4 6 - 2 - 3 0 0 0

PIPE SIZE

C = 1" (25mm)
E = 1-1/2" (40mm)
F = 2" (50mm)

BODY SIZE (Reference only)

1 = 1"
4 = 1-1/2"
5 = 2"

END CONNECTIONS

0 = Female N.P.T. 3 = Flanged / Female N.P.T. Boss Taps

BODY & CAP MATERIAL

2 = 316 Stainless Steel (Cast CF8M)

VALVE OPTIONS (00 = Standard)

00 = NO 11 = NO, LS, SAO
01 = NO, SAO 30 = NC
02 = NO, SAC 32 = NC, SAC
10 = NO, LS 40 = NC, LS

SEAL MATERIALS (0 = Standard) (Option 5 not valid for NC valves)

OPT.	OPERATING DIAPHRAGM	SEALING DISK	DYNAMIC SEAL	STATIC SEALS	MAX TEMPERATURE
0	Buna-N	Buna-N	Buna-N	Buna-N	150° (65°C)
1	Buna-N	EPDM	EPDM	EPDM	200° (93°C)
2	FKM	FKM	FKM	FKM	250° (121°C)
4	FKM	EP	EP	EP	200° (93°C)
5	Buna-N	FKM	FKM	FKM	200° (93°C)

INTERNAL PARTS

3 = 316 Stainless Steel

* To create a valve number replace each "_" with the proper number or letter for the feature you desire. For example, a 1" NPT Stainless Steel Valve Model V461 with Normally Closed and Spring Assist Closed Options is designated as a V46C-0232-03000.

REV.	ECO NO.	DESCRIPTION	BY/DATE
C	21190	Reviewed for Pentair ECN release	JJJ 17-Nov-09
D	103533	REM'D:FEMALE BSPT (TAPERED) THD OPTION	TJM 20-Jun-14
E	1778	TOOK OUT OPTION 6 (SEAL MATERIAL)	MM OCT-1-2020
F	2177	BRANDING UPDATE	JJJ 2-Jan-23

42988